

Two Wheel Drive Factory Stock 6500

1. Must be factory stock and can have fuel injection if factory.
2. Must be factory installed engine for the year model of truck.
3. Must have current registration and insurance to match vehicle.
4. Can have headers and factory aluminum intake and ladder bars.
5. Production 2WD frame and no larger than 1-Ton drivetrain.
6. Factory located reese hitch or bumper with 30-inch max hitch height and removable pins.
7. HOOK POINT MUST BE HORIZONTAL WITH A 3.5 INCH HOLE.
8. D.O.T. max 35-inch tires, unaltered.
9. No hanging weights
10. No power adders.
11. Must have exhaust past cab with muffler.
12. Must retain factory suspension with no type of clamps, races or chains to the axel frame or hitch.
13. Absolutely no passengers allowed.
14. Truck Pull Track Committee has final say on all rules.
15. If more than half of the pullers in the class file a complaint, truck is subject to re-inspection.

Pull Track tech committee haves final say on all rules!

Street diesel 8500/9500

1. Must have license & insurance (must belong to Vehicle Pulling)
2. No Hanging Weights and all weights must be no farther forward than the firewall.
3. Can have traction bars (Must be pinned and removable not welded)
4. Can have rear blocked (Must be pinned and removable not welded)
5. Can have tuner.
6. Can have upgraded exhaust but must exit behind cab.
7. Must have factory equipped OEM turbocharger (absolutely no modified 'stock appearing' or s300/s400/s500 turbo chargers allowed)
8. Can have cold air intake.
9. Maximum twenty-six inches hitch height and must have a three-inch horizontal opening. Must be a factory Reese hitch in factory location.
10. Can have aftermarket lift pump.
11. No injectables
12. No sanctioned trucks allowed.
13. Must be a 1 ton or smaller drive train.
14. Factory dually allowed and all tires must be the same size.
15. No adapters and spacers
16. All safety equipment is STRONGLY SUGGESTED

Pull Track tech committee has final say on all rules!

Modified Gas 6200/6500

1. Can have aftermarket heads.
2. Can have your choice of any single carb.
3. Can have Electric water pump
4. Can have electric fans
5. Can have headers
6. Can have aluminum intake
7. Must have kill switch
8. Must have driveshaft loops and Ujoint shields
9. MUST be DOT tires and no bigger than 33/12.50
10. Maximum twenty-six inches hitch height and must have a three-inch horizontal opening.
11. Must remain full bed and cab.
12. Exhaust is optional
13. 1 ton and smaller driveline
14. No Rigid Suspension trucks allowed Can have traction bars and suspension stops (pinned or bolted NOT WELDED must be removable)
15. No Pro Stock
16. No Tilt Body
17. Sanction trucks are welcome.

All safety equipment is **STRONGLY SUGGESTED**
Pull Track tech committee has final say on all rules!



Pull Track Tech Committee has final say on all rules!

Two Wheel Drive Factory Stock 6500

1. Must be factory stock and can have fuel injection if factory.
2. Must be factory installed engine for the year model of truck.
3. Must have current registration and insurance to match vehicle.
4. Can have headers and factory aluminum intake and ladder bars.
5. Production 2WD frame and no larger than 1-Ton drivetrain.
6. Factory located reese hitch or bumper with 30-inch max hitch height and removable pins.
7. HOOK POINT MUST BE HORIZONTAL WITH A 3.5 INCH HOLE.
8. D.O.T. max 35-inch tires, unaltered.
9. No hanging weights
10. No power adders.
11. Must have exhaust past cab with muffler.
12. Must retain factory suspension with no type of clamps, races or chains to the axel frame or hitch.
13. Absolutely no passengers allowed.
14. Truck Pull Track Committee has final say on all rules.
15. If more than half of the pullers in the class file a complaint, truck is subject to re-inspection.

Pull Track tech committee has final say on all rules!

Two Wheel Drive Modified
~~6500~~

Two Wheel Drive Modified 6500

1. Bring what you brought.
2. Highly recommend drive shaft loops and kill switch.
3. Absolutely no passengers allowed.
4. Truck Pull Track Committee has final say on all rules.

Pull Track tech committee has final say on all rules!

Factory Stock Gas 6500/7000

1. Must have license & insurance (must belong to Vehicle Pulling)
2. Must have fuel Tank in Factory location.
3. Must have exhaust with mufflers, no headers unless from factory. Exhaust must not exceed two- and half-inch OD.
4. No Hanging Weights and all weights must be no farther forward than the firewall.
5. Must have Factory Ignition, no MSD or similar ignition box. (Can run MSD Distributor)
6. Maximum twenty-six inches hitch height and must have a three-inch horizontal opening.
7. Pump Gas only. (85,87 or 93 octane)
8. No traction bars.
9. Must be factory suspension, without blocks.
10. Dually's must drop 200 lb. or three inch of hitch height.
11. Must be a Factory removable Reese style or bump hitch with a three-inch horizontal opening.
12. No turbo or nitrous
13. No Sanction Trucks.
14. Must have 1 ton or smaller drivetrain.

Pull Track tech committee has final say on all rules!

Modified Diesel 8500/9500

1. Suspension stops and traction bars allowed but must be removable CAN NOT BE RIGET
2. Driveshaft loops and shields not required but highly recommended.
3. Open fuel and air
4. No injectables allowed.
5. Hanging weights allowed
6. No ag governors
7. Transmissions blankets not required but highly recommended.
8. Maximum twenty-six inches hitch height and must have a three-inch horizontal opening.
9. Must be a 1 ton or smaller drive train.
10. Hanging weight can't be farther than 60 inches from front axle.
11. All safety equipment is STRONGLY SUGGESTED

Pull Track tech committee has final say on all rules!

Street Gas 6500/7000

1. Must have license & insurance (must belong to Vehicle Pulling)
2. Must have OEM cast iron cylinder heads (NO ALUMINUM HEADS UNLESS FACTORY TO THE ENGINE)
3. Must have Factory located fuel tank.
4. Can have maximum of 1 3/4 Header.
5. Can have aluminum intake.
6. Can have cold air intake.
7. Electronic fuel injection trucks can run two modifications to the engine. Description of modification are (tuners, cold air intake, header, carburetor swap and ext.)
8. Can have traction bars and suspension stops (pinned or bolted NOT WELDED must be removable)
9. Can run MSD ignition.
10. Can have hanging weights but must be removable.
11. Maximum exhaust size is three-inch pipe pass the cab.
12. Maximum twenty-six inches hitch height and must have a three-inch horizontal opening.
13. NO DRAW BAR HITCHES
14. Must have three-eighths fuel lines or smaller/ -6an fuel line.
15. Can run electric fuel pump.
16. No electric water pumps.
17. No turbos or nitrous
18. No slipper clutches or lock up converter's switches.
19. Dually's must drop 200 lb. or three inch of hitch height.
20. Recommend u-joint shields and driveshaft loops.
21. Pump Gas only. (85,87 or 93 octane)
22. NO SANCTIONED TRUCKS
23. Must have 1 ton or smaller drivetrain.
24. All safety equipment is STRONGLY SUGGESTED

Pull Track tech committee haves final say on all rules!

Open Modified Gas 6200/6500

1. Run what you bring gas!
2. Power adders allowed.
3. Open Driveline
4. Must have driveshaft loops and u joint shields.
5. Must have kill switch.
6. All safety equipment is **STRONGLY SUGGESTED**
7. Pro stock allowed.

Pull Track tech committee has final say on all rules!

Farm Truck 6500/7000

1. Must have insurance (must belong to Vehicle Pulling)
2. Must have fuel tank in factory location.
3. Can have Headers.
4. Can have Aluminum intake but must retain factory block for the year and make of the vehicle.
5. Can have cold air intake.
6. NO DOMINATORS CARBURETOR
7. Can have big block swap.
8. Can have traction bars and suspension stops (pinned or bolted NOT WELDED must be removable)
9. Can run MSD ignition.
10. No Hanging Weights and all weights must be no farther forward than the firewall.
11. Maximum exhaust size is three-inch pipe pass the cab.
12. Must have a Carburetor or throttle body only. (NO Mass FLOW)
13. Maximum twenty-six inches hitch height and must have a three-inch horizontal opening.
14. NO DRAW BAR HITCHES
15. Can run electric fuel pump.
16. No turbo and nitrous.
17. Dually's must drop 200 lb. or three inch of hitch height.
18. Recommend u-joint shields and driveshaft loops.
19. Pump Gas only. (85,87 or 93 octane)
20. No electric water pumps.
21. No Sanctioned Trucks
22. Pined suspension allowed but must be removable without welds.
23. Must have 1 ton or smaller drivetrain.

Pull Track tech committee hases final say on all rules!

Factory stock diesel 8500/9500

1. Must have license & insurance (must belong to Vehicle Pulling)
2. No tuners
3. No Hanging Weights and all weights must be no farther forward than the firewall.
4. No aftermarket fuel systems (fass/air dog)
5. 35/12.50 tire max
6. Maximum twenty-six inches hitch height and must have a three-inch horizontal opening.
7. Exhaust must exit in the factory location.
8. No injectables
9. No sanctioned trucks
10. Factory ~~Daullys~~ allowed.
11. No adapters and spacers.
12. All safety equipment is **STRONGLY SUGGESTED**

Pull Track tech committee haves final say on all rules!

Super Street Gas 6500/7000

1. Must have license & insurance (must belong to Vehicle Pulling)
2. Must have OEM cast iron cylinder heads (NO ALUMINUM HEADS UNLESS FACTORY TO THE ENGINE)
3. Can have headers.
4. Can have aluminum intake.
5. Can have cold air intake.
6. Can have tuner on factory fuel injection engine.
7. Can have traction bars.
8. Can run rear suspension blocks but must be able to remove them.
9. Can have max 3.5 inches Exhaust behind cab (mufflers optional)
10. Can have hanging weights, but no more than sixty inches from front axle.
11. No cutting or gutting of body EXCEPT for header clearance!
12. Maximum tire size 33x12.50 or metric 315/65r17, 295/65r18, 325/50r20
13. Maximum twenty-six inches hitch height , must be a reese style hitch and must have a three-inch horizontal opening. Hitch may be reinforced but CAN NOT HAVE SUPPORTS GOING TO AXLE AND ABSOLUTELY NO DRAW BAR HITCH
14. MAX 133 inches wheel bases
15. Racing fuel is allowed.
16. 4150 flange carb (no dominators)
17. Can have fuel cell.
18. Can have an electric fuel pump.
19. Can run electric fans.
20. No electric water pumps.
21. No turbos or nitrous
22. NO SANCTIONED TRUCKS
23. Must have 1 ton or smaller drivetrain.
24. All safety equipment is STRONGLY SUGGESTED

Pull Track tech committee haves final say on all rules!

Super Street Diesel 8500/9500

1. Must have license & insurance (must belong to Vehicle Pulling)
2. Can run hanging weight but must be removable.
3. Can have modified fuel and air (No s400 or larger chargers allowed)
4. Exhaust must exit behind cab.
5. Suspension stops allowed but must be removable (Pin or bolted only!)
6. Traction bars allowed but must be removable (Pin or bolted only!)
7. Maximum twenty-six inches hitch height and must have a three-inch horizontal opening. Hitch may be reinforced but CAN NOT HAVE SUPPORTS GOING TO AXLE AND ABSOLUTELY NO DRAW BAR HITCH
8. No injectables
9. No sanctioned trucks
10. Factory dually allowed and all tires must be the same size.
11. Must be a 1 ton or smaller drive train.
12. Hanging weight cannot be farther than 60 inches from front axle
13. All safety equipment is **STRONGLY SUGGESTED**

Pull Track tech committee has final say on all rules!

Open Gas or Diesel 10,000

Run what you bring gas or diesel

Only regulation is weight

All safety equipment is **STRONGLY SUGGESTED**

Pull Track tech committee has final say on all rules!

